

# JALASKA SAS 00J0266

**S3 SRC**  
**EN ISO 20345:2011**  
**36 to 48**

Distributed by:



- Full grain **AP 23** leather
- **Softane™** dual-density sole
- Steel toe cap / Steel midsole
- Antistatic

- ❖ Natural-coloured boot with 2 leather side tabs for rapid pull-on.
- ❖ Boot in full grain leather **AP 23**, water and oil resistant : a Jallatte exclusive
  - **10 to 15% thicker** (2.4mm) than most leathers usually used in safety shoe manufacture.
  - **Upper resistance to water penetration**: to European standard level or more.
- ❖ Flat binding at top of quarters.
- ❖ Full-size inlay, removable, anti-bacterial treated, anatomical and comprising heel shock absorber. High capacity to absorb and desorb perspiration.
- ❖ Forefoot lining, resistant to abrasion and perspiration acids.
- ❖ Perforated steel toe-cap (patented) – 200 J.
- ❖ Puncture-resistant stainless steel midsole .
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Dual density **Softane™** sole with progressive shock absorber to protect back and joints from vibrations. Self cleaning sole pattern. Multi-directional treads. Rounded heel pressure zone for comfort and stability

## Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic/lubricant : water and detergent

On flat **0,58** (>0,32) – On the heel **0,54** (>0,28)

**SRB** Test ground steel/lubricant : glycerine

On flat **0,37** (>0,18) – On the heel: **0,14** (>0,13)

- ✓ Wraps round the foot for increased stability when walking.
- ✓ Outsole density = 1.02 / Comfort layer density = 0.45
- ✓ Highly resistant to oils and hydrocarbons.
- ✓ Abrasion resistance : 80 mm<sup>3</sup>
- ✓ Heel shock absorption 29 Joules.

Weight	Gross weight (42): 1740 g / Net weight (42): 1420 g
Size	36 to 48
Packaging	5 pairs
Box shoes (mm)	337 x 328 x 135
Cartons (mm)	625 x 425 x 345

Non contractual document  
Copyright JALLATTE  
Controlled distribution

01/10/2021

