

GUANTE JUBA - 406RF WINTER JUBA

Grain cow leather with cotton liner docker glove



NORMATIVE



FEATURES

- Flexibility and tactility.
- Economy design.
- Cotton liner provides comfort and thermal protection against coldness.
- Individually packed pairs with header card for retail.

MORE INFO

Materials	Colour	Thickness	Length	Sizes	Packaging
Leather	Yellow	1.20 mm	M - 24 cm L - 25 cm XL - 26 cm XXL - 27 cm	8/M 9/L 10/XL 11/XXL	12 pairs/package 60 pairs/box

Distributed by:



NORMATIVAS



EN 511:2006



Levels vs temperature of glove use

If the convective cold is level 0 - This glove can be used up to a temperature of 0°C

If the convective cold is level 1 - This glove can be used up to a temperature of -10°C

If the convective cold is level 2 - This glove can be used up to a temperature -20°C

If the convective cold is level 3 - This glove can be used up to a temperature of -30°C

If the convective cold is level 4 - This glove can be used up to a temperature of -40°C

Gloves on both hands must meet the requirements below:

Performance level		1	2	3	4
A convective cold resistance*	ltr thermal insulation in m ² °C/w	0,10 ≤ itr ≤ 0,15	0,15 ≤ itr ≤ 0,22	0,22 ≤ itr ≤ 0,30	0,30 ≤ itr
B contact cold resistance	Thermal resistance r in m ² c/w	0,025 ≤ r ≤ 0,050	0,050 ≤ r ≤ 0,100	0,100 ≤ r ≤ 0,150	0,150 ≤ r
C water impermeability	Waterproof for at least 30 minutes	Pass			


EN388:2016



EN388:2016 Protective gloves against mechanical risks.

The EN388: 2003 standard is renamed EN388: 2016, the year of its revision. The reason for the modification is given by the discrepancies in the results between laboratories in the knife cut test, COUP TEST. Materials with high levels of cut produce a dulling effect on the circular blades, which undermines the result.

The new regulation was published in November 2016 and the previous one is from the year 2003. During these 13 years, there has been a great innovation in the materials for the manufacture of cutting gloves, they have forced to introduce changes in the tests to be able to measure with more rigorous levels of protection. If you want to know more about the main changes in these regulations, you can consult it through our website www.jubappe.es



- A - Abrasion resistance (X, 0, 1, 2, 3, 4)
- B - Blade Cut Resistance (X, 0, 1, 2, 3, 4, 5)
- C - Tear resistance (X, 0, 1, 2, 3, 4)
- D - Puncture resistance (X, 0, 1, 2, 3, 4)
- E - Cutting by sharp objects ISO 13997 (A, B, C, D, E, F)
- F - Impact test complies / does not comply (It is optional. If it complies, put P)

En388:2016 performance levels	1	2	3	4	5
6.1 abrasion resistance (cycles)	100	500	2000	8000	-
6.2 blade cut resistance (index)	1,2	2,5	5	10	20
6.4 tear resistance (newtons)	10	25	50	75	-
6.5 puncture resistance (newtons)	20	60	100	150	-

Eniso13997:1999 performance levels	A	B	C	D	E	F
6.3 tdm: cut resistance (newtons)	2	5	10	15	22	30

Distributed by:

