

Distributed by:



LIGHT PLUS 5

- Dorsal anchorage ring.
- 2 sternal A/2 anchorage rings.
- Dorsal extension strap included.
- Adjustable on shoulders, thighs and chest.
- NFC ready: Incorporates the new Irucheck NFC technology.

Materials

Tape	Polyester
Thread	High tenacity polyamide
Rings	Steel
Buckles	Steel

Estándar	EN 361
Size	UNIVERSAL
Weight	900 g
Harness strength	>15 kN
Ring resistance	22 kN
Antislip System	No
Belt width	44 mm
Load	140 Kg
Lifetime (years)	10 in use + 2 in storage from manufacture



SCREW-LOCK



STEELSAFE 981

Steel connector with manual threaded lock.

Norm	EN 362
Weight	174 g
Opening	18 mm
Closure	Screw-Lock (manual thread)
Resistance	25 kN
Lifetime (years)	Unlimited

Distributed by:



Material

Body	Steel
Thread	Steel



ABE 361

- Energy absorber with semi-static rope.
- Designed to withstand falls.
- Reduces the impact of falling below 6 kN.
- Rope ends sewn and covered with polyethylene material, abrasion resistant thimbles.

Distributed by:



www.irudek.com

Norm	EN355
Length	150 cm
Weight	450 g
Diameter	11 mm
Static resistance	25 kN
Stopping distance	1 m
Lifetime (years)	10 of use + 1 of storage
Materials	
Rope	Polyamide
Absorber	Polyester



LIGHTBAG

- Small 10 liter carrying bag for PPE's.
- It has cordino handles for shoulder transport.

Capacity	10 L
Shoulder pads for the back	Yes

Distributed by:

