

GUANTE JUBA - MT180 POWER CUT

Goat skin with reinforcements on palm and elasticated wrist. Chainsaw cut protection on the back.



Distributed by:



NORMATIVE



CHARACTERISTICS

- Inner nylon® elastic fist and velcro fastener on the sleeve for a better fit.
- Sewn with para-aramid (Kevlar®) thread to make the seams stronger.
- Long sleeve for greater protection.
- The back is made of 12 different layers of fabric (hide and synthetic fabrics) to protect users from chainsaws.

WORKING GLOVES SUITABLE FOR:

- Handling jobs using chainsaws.
- Forestry and environmental conservation jobs.

MORE INFO

Materials	Colour	Length	Sizes	Packaging
Leather	Beige / Brown	M - 33 cm XXL - 36 cm	8/M 11/XXL	1 pairs/package 50 pairs/box

NORMATIVAS



EN 381-7:1999



CLASE X

Class	Speed
0	16 m/s
1	20 m/s
2	24 m/s
3	28 m/s

EN 381-7:1999 – Chainsaw risks

The minimum levels required for the EN388 standard are as follows:

Abrasion resistance **2**

Cut resistance **1**

Tear resistance **2**

Puncture resistance **2**

Protection against cutting by chain saws:


EN388:2016



EN388:2016 Protective gloves against mechanical risks.

The EN388: 2003 standard is renamed EN388: 2016, the year of its revision. The reason for the modification is given by the discrepancies in the results between laboratories in the knife cut test, COUP TEST. Materials with high levels of cut produce a dulling effect on the circular blades, which undermines the result.

The new regulation was published in November 2016 and the previous one is from the year 2003. During these 13 years, there has been a great innovation in the materials for the manufacture of cutting gloves, they have forced to introduce changes in the tests to be able to measure with more rigorous levels of protection. If you want to know more about the main changes in these regulations, you can consult it through our website www.jubappe.es



- A - Abrasion resistance (X, 0, 1, 2, 3, 4)
- B - Blade Cut Resistance (X, 0, 1, 2, 3, 4, 5)
- C - Tear resistance (X, 0, 1, 2, 3, 4)
- D - Puncture resistance (X, 0, 1, 2, 3, 4)
- E - Cutting by sharp objects ISO 13997 (A, B, C, D, E, F)
- F - Impact test complies / does not comply (It is optional. If it complies, put P)

En388:2016 performance levels	1	2	3	4	5
6.1 abrasion resistance (cycles)	100	500	2000	8000	-
6.2 blade cut resistance (index)	1,2	2,5	5	10	20
6.4 tear resistance (newtons)	10	25	50	75	-
6.5 puncture resistance (newtons)	20	60	100	150	-

Eniso13997:1999 performance levels	A	B	C	D	E	F
6.3 tdm: cut resistance (newtons)	2	5	10	15	22	30

Distributed by:

