

GUANTE GUANTES DE PVC JUBA - NI00 NINJA ICE

7 gauge acrylic terry liner on the inside and a 15 gauge Nylon® liner with HPT™ half coating.



NORMATIVE



Distributed by:



CHARACTERISTICS

- Interior with vulrizo finish that protects against cold and low temperatures (0°C).
- PVC coated palm with HPT (Hydropellent Technology) technology that repels liquids in moderate situations, and provides excellent grip in dry or humid environments.
- Great resistance and very durable.
- Suitable for food use.

WORKING GLOVES SUITABLE FOR:

- Cold zone replenishers.
- Exterior work.
- Cold rooms and frozen.
- Building.
- Carretilleros.
- Handling of frozen food.
- Transport of refrigerated merchandise.
- Farming.

MORE INFO

Materials	Colour	Thickness	Length	Sizes	Packaging
Pvc	Black	Gauge 15	XS - 23 cm S - 24 cm M - 25 cm L - 26 cm XL - 27 cm XXL - 29 cm	6/XS 7/S 8/M 9/L 10/XL 11/XXL	6 pairs/package 72 pairs/box

Distributed by:



NORMATIVAS



EN 511:2006



Levels vs temperature of glove use

If the convective cold is level 0 - This glove can be used up to a temperature of 0°C

If the convective cold is level 1 - This glove can be used up to a temperature of -10°C

If the convective cold is level 2 - This glove can be used up to a temperature -20°C

If the convective cold is level 3 - This glove can be used up to a temperature of -30°C

If the convective cold is level 4 - This glove can be used up to a temperature of -40°C

Gloves on both hands must meet the requirements below:

Performance level		1	2	3	4
A convective cold resistance*	ltr thermal insulation in m ² °c/w	0,10 ≤ itr ≤ 0,15	0,15 ≤ itr ≤ 0,22	0,22 ≤ itr ≤ 0,30	0,30 ≤ itr
B contact cold resistance	Thermal resistance r in m ² c/w	0,025 ≤ r ≤ 0,050	0,050 ≤ r ≤ 0,100	0,100 ≤ r ≤ 0,150	0,150 ≤ r
C water impermeability	Waterproof for at least 30 minutes	Pass			


EN388:2016



EN388:2016 Protective gloves against mechanical risks.

The EN388: 2003 standard is renamed EN388: 2016, the year of its revision. The reason for the modification is given by the discrepancies in the results between laboratories in the knife cut test, COUP TEST. Materials with high levels of cut produce a dulling effect on the circular blades, which undermines the result.

The new regulation was published in November 2016 and the previous one is from the year 2003. During these 13 years, there has been a great innovation in the materials for the manufacture of cutting gloves, they have forced to introduce changes in the tests to be able to measure with more rigorous levels of protection. If you want to know more about the main changes in these regulations, you can consult it through our website www.jubappe.es



- A - Abrasion resistance (X, 0, 1, 2, 3, 4)
- B - Blade Cut Resistance (X, 0, 1, 2, 3, 4, 5)
- C - Tear resistance (X, 0, 1, 2, 3, 4)
- D - Puncture resistance (X, 0, 1, 2, 3, 4)
- E - Cutting by sharp objects ISO 13997 (A, B, C, D, E, F)
- F - Impact test complies / does not comply (It is optional. If it complies, put P)

En388:2016 performance levels	1	2	3	4	5
6.1 abrasion resistance (cycles)	100	500	2000	8000	-
6.2 blade cut resistance (index)	1,2	2,5	5	10	20
6.4 tear resistance (newtons)	10	25	50	75	-
6.5 puncture resistance (newtons)	20	60	100	150	-

Eniso13997:1999 performance levels	A	B	C	D	E	F
6.3 tdm: cut resistance (newtons)	2	5	10	15	22	30

Distributed by:

