

GUANTE JUBA - NX400 NINJA X4

13 gauge Nylon® and fiberglass shell with bi-polymer (PU and Nitrile) coating on palm and fingers.



Distributed by:



NORMATIVE



CHARACTERISTICS

- Made with a fibreglass liner on the inside and Nylon® liner on the outside for medium risk of cutting.
- Revolutionary bi-polymer dip on palm and fingers to achieve PU's flexibility and feel and nitrile's mechanic resistance.
- Excellent resistance to abrasion.
- Silicone free synthetic yarn.
- DMF free.
- The Sanitized® hygiene function protects gloves from the formation of fungi, mites and bacteria, prevent odors, provides long-lasting material protection to polymers and minimize skin irritation.

WORKING GLOVES SUITABLE FOR:

- Machining of parts.
- Automotive.
- Aeronautics.
- Plate handling.
- Canning.
- Bottling plants.

MORE INFO

Materials	Colour	Thickness	Length	Sizes	Packaging
Nitrile / polyurethane	Mottled / Black	Gauge 10	XS - 22 cm	6/XS	12 pairs/package
			S - 23 cm	7/S	144 pairs/box
			M - 24 cm	8/M	
			L - 25 cm	9/L	
			XL - 26 cm	10/XL	
			XXL - 27 cm	11/XXL	

NORMATIVAS


EN388:2016



EN388:2016 Protective gloves against mechanical risks.

The EN388: 2003 standard is renamed EN388: 2016, the year of its revision. The reason for the modification is given by the discrepancies in the results between laboratories in the knife cut test, COUP TEST. Materials with high levels of cut produce a dulling effect on the circular blades, which undermines the result.

The new regulation was published in November 2016 and the previous one is from the year 2003. During these 13 years, there has been a great innovation in the materials for the manufacture of cutting gloves, they have forced to introduce changes in the tests to be able to measure with more rigorous levels of protection. If you want to know more about the main changes in these regulations, you can consult it through our website www.jubappe.es



A - Abrasion resistance (X, 0, 1, 2, 3, 4)
 B - Blade Cut Resistance (X, 0, 1, 2, 3, 4, 5)
 C - Tear resistance (X, 0, 1, 2, 3, 4)
 D - Puncture resistance (X, 0, 1, 2, 3, 4)
 E - Cutting by sharp objects ISO 13997 (A, B, C, D, E, F)
 F - Impact test complies / does not comply (It is optional. If it complies, put P)

En388:2016 performance levels	1	2	3	4	5
6.1 abrasion resistance (cycles)	100	500	2000	8000	-
6.2 blade cut resistance (index)	1,2	2,5	5	10	20
6.4 tear resistance (newtons)	10	25	50	75	-
6.5 puncture resistance (newtons)	20	60	100	150	-

Eniso13997:1999 performance levels	A	B	C	D	E	F
6.3 tdm: cut resistance (newtons)	2	5	10	15	22	30

Distributed by:

